

SBT3000S

The SBT3000S Cylindrical Swing Barrier is a small cost-effective entry control system specifically designed for confined areas.



The SBT3000S offers a single-lane or dual-lane swing barrier designed for smooth and quiet operation and draws very little power. The width of the lane is 600mm. The fastest the gate opening/closing time can be 1 seconds. Besides, during a power outage, the door can be opened manually for users to enter and exit freely. Suitable for some office buildings, commercial service places and other high-end places

Features

- Fast and accurate, the fastest opening time can be up to 1s-10s
- Power outage can be opened manually, automatic closing during power on
- Prevent collision, anti intrusion
- Super bright direction indicator indicates traffic status
- Can be one-way or two-way control personnel in and out

Specifications

Model	SBT3000S
Power Requirements	AC 110V/220V, 50/60Hz
Operating Voltage	Stand by 60W Working 135W
Lane Width (mm)	Single: 600 (Optional: 800) Double machine: 600 (Optional: 900)
LED Indicator	Support
Cabinet Material	SUS304 stainless steel
Lid Material	SUS304 stainless steel
Barrier Material	Acrylic
Barrier Movement	Swing
Emergency Mode	Support
Working Temperature	-15°C to 60°C
Working Humidity	20% to 93% (non-condensing)
Working Environment	Indoor
Dimensions (L*H)	127*1005mm(Single)
Dimensions with Packing (L*W*H)	113*32*78mm(Dual)
Weight (kg)	100kg(Dual)
Weight with Packing (kg)	125kg(Dual)
MCBF	3million

Dimensions (mm)

