

QR500 Series Reader

Wiegand & RS485 QR code Reader



The QR code Reader is a new generation of intelligent access control card reader. It has fast scanning speed, high recognition rate, High compatibility, and can be connected to any access controller that supports Wiegand input. It also support the RFID Functions, like 13.56MHz Mifare Ultralight / DESFire EV1, NTag, So that it can be applied in community management, visitor management, hotel management, unmanned supermarkets and so on.

Features

- QR Code、Data Matrix、PDF417、GS1 Databar、Code 128/EAN128、UPC/EAN、Codabar、Code 39/93 etc.
- Mifare Ultralight / S50 / S70 / DESFire EV1 / NTag
- Reading Distance: QR ≤ 5CM, RFID Card ≤ 4CM
- W26 / W34 / W66, RS485, USB

Specifications

International Standard	ISO / IEC 14443A RS485 Protocol	Communication	Wiegand, RS485, USB
Barcode	QR、DataMatrix、PDF417、GS1 Databar、Code 128/EAN128、UPC/EAN、Codabar、Code 39/Code 93 etc.	Operating Temperature	-10C° ~ 50C°
RFID	Mifare Ultralight, DESFire EV1, Ntag, S50 / S70	Storage Temperature	-20C° ~ 80C°
Operating Frequency	13.56MHz	Operating Humidity	20% - 80%
Power	DC 12V (±5%), USB 5V	Dimensions	86*86*50 mm
Operating Distance	QR ≤ 5CM, RFID Card ≤ 4CM	USB Cable	1000mm

Reader List

- QR500-B ERP Code: X02101088
- QR500-W ERP Code: X02101089